Departement of the Environment, Transport, Energy and Communications

Swiss Federal Office of Energy SFOE

## CO<sub>2</sub> GEOTHERMAL HEAT PROBE

## PHASE 2

## **Annual Report 2008**

Author and Coauthors Dr. Andrea Grüniger, Dr. Beat Wellig

Company / Institution Lucerne University of Applied Sciences and Arts – Engineering &

Architecture, CC Thermal Energy Systems & Process Engineering

Address Technikumstrasse 21, CH-6048 Horw

Phone, e-mail, Internet +41 41 349 32 57, beat.wellig@hslu.ch, www.hslu.ch/tevt

SFOE Project/Contract-number 102'247 / 152'857

SFOE-Project Coordinator Th. Kopp, Head of R&D Program, Heat Pumping Technologies,

Cogeneration, Refrigeration' of SFOE

Project Duration (Start-End) August 2007 – August 2009

Date of Report 8 December 2008

## **SUMMARY**

In this project the fluid dynamics and thermodynamics inside a  $CO_2$  geothermal heat probe have been investigated. The functionality of such a probe, which works like a thermosyphon, was analyzed by means of a simulation model in MATLAB. The model couples the behaviour inside the heat probe with the heat conduction in the earth. A parameter study revealed that the self-circulation character of such a probe leads to flattening of the vertical earth temperature profile near the probe and, hence, leads to more uniform heat removal along the probe. This "energy shifting effect" from bottom to top even works when the heat pump is off, by a combination of evaporation of  $CO_2$  in the lower part and condensation in the upper part of the probe. The heat transfer resistance of the evaporating  $CO_2$  film flowing down the probe wall is very small compared to the conduction resistance of the earth. Therefore, no difference has been found between the performances of a conventional heat pipe and a configuration where the liquid phase injection is distributed on different height stages along the probe. By dimensioning a  $CO_2$  heat pipe it has to be considered that the pipe diameter has to be wide enough in order to not limit the heat flow due to flooding (holdup of liquid film by gas flow). Wider pipes are also favourable regarding heat transfer, while on the other hand costs of construction will increase.